



PRODUCT NO.: 6405



MAZERUSTAR PLANETARY MIXER (1 kg × 2)

Model KK-1000W, W 22.2" × D 23.5" × H 27.6"

DESCRIPTION: The Mazerustar is an integrated mixer and a deaerator system designed to perform both mixing and deaeration while simultaneously rotating and revolving the containers. This unique motion eliminates the need for mixing rods, blades and an evacuation device, thus reducing processing times.

The system is most effective for the following materials and processing purposes:

- ✔ High-viscosity liquids that cannot be processed or take a long time to mix or deaerate when a conventional mixer or deaerator is used
- ✔ Uniform mixing/dispersion of materials having a great difference in blending ratios and specific gravity when the liquids are mixed with each other, or when a liquid is mixed with powder/filler
- ✔ Materials that need to be processed with minimal waste and contamination (by foreign matter) because they have high added value
- ✔ Operation processes in which it is desirable to eliminate steps involving the cleaning of the system and containers

Comes with: Standard Mixing Container (4), Disposable Liner (10), Hex Wrench, Power cord and Manual

FEATURES:

- ✔ Ideal for mixing creams, gels, ointments and liquids
- ✔ Includes a vacuum-like feature to help remove air entrapment
- ✔ Ensures homogeneous formulations
- ✔ Operates with redundant safety features
- ✔ Reusable and disposable containers allow for quick and easy clean-up
- ✔ Saves time and money with efficient mixing process
- ✔ Lightweight, bench-top model
- ✔ No mixing rods or blade; reduced risk for cross contamination

TECHNICAL SPECIFICATIONS:

External Dimensions, W × D × H (mm / in)	565 × 597 × 700 / 22 × 24 × 28
Weight (kg / lb)	~ 120 / 265
Processing capacity	1 kg × 2 cups
Cup/Container Weight	170 g
Standard container	1.1 L / 37.2 oz dedicated container made of HDPE
Power consumption	~ 2 kW
Power Supply	AC200 V ±10%
Operating temperature / humidity	10 – 40°C, 20 – 80% RH
Number of channels	20 (10 fixed, 10 User defined)
Step time	10 – 990 seconds × 3 steps
Safety functions	Automatic shutoff in case of any errors Door interlocks prevents the system from operating while upper door is open
Warning functions	Unbalanced load warning Non-secured door warning Non-secured maintenance cover warning Overload warning
Rotation	10 levels variable (0 – 9) (1 times revolution except 0 speed)
Revolution	9 levels variable

WARRANTY: 1 year